

Wind Speed Indicator & Wind Display

Key Features

- Digital Output
- 0-359° wind direction
- 2/10 Min & User Average
- Wind Variation
- Maximum Gust
- M/S, Knots, MPH, KM/H & Beaufort
- Optional Auto/Manual Brightness Control
- Resolution WVGA 800x480

The Gill Instruments Meteorological TFT WindDisplay is a combined wind speed and direction indicator. Wind information is displayed using on a 8.5" LED backlight, industrial grade, LCD screen and the data will be indicated with a true viewing angle of 170°.

The Meteorological TFT WindDisplay has been designed to operate with the Gill WindObserver and WindSonic wind sensors. Meteorological TFT WindDisplay receives data directly from the wind sensor in NMEA mode without the need for additional interfaces. It provides the power supply for the wind sensor and can be "daisy chained" to a second wind display to transfer wind sensor information.

Also suitable for 144x144 mm instrument replacement (portrait or landscape)¹



DISPLAY

Speed Display	Central, 3 digit, 11mm height
Gust Display	3 digit, 8mm height
Average	2 minutes, 10 minutes, User defined
Other	Wind Variance

WIND SPEED

Units	mph, m/s, knots, km/h, Beaufort
-------	---------------------------------

DIRECTION

Direction display	Left hand side, 3 digit, 8mm height
Direction average	Grey arrow indicator on the display and value in the direction display

INPUT /OUTPUT

Input	NMEA (output from Gill anemometer)
Output	+15 VDC Sensor supply RS422 daisy chain output
Formats	NMEA 4800 Baud

POWER REQUIREMENT

Power supply	100 to 240 Vac, 50/60 Hz, max 50 VA. Option for 18-32Vdc
--------------	---

MECHANICAL

Size	238 x 148.5 x 71 mm
Weight	1.2kg

ENVIRONMENTAL

Humidity	10% to 93% RH
Operational Temperature	-15°C to +55°C
Moisture Protection	IP22
EMC	ESD IEC 61000-4-2 Radiated Immunity IEC 61000-4-3 Conducted Immunity IEC 61000-4-6 Fast Transients IEC 61000-4-4 Surge IEC 61000-4-5

Typical Applications

- Meteorological/Hydrological
- Aviation/Industrial/Transport/Construction

Gill Instruments Limited

Saltmarsh Park, 67 Gosport Street
Lymington, Hampshire SO41 9EG
United Kingdom

Tel: +44 (0) 1590 613 500
Fax: +44 (0) 1590 613 501
contact@gillinstruments.com

gillinstruments.com

1086-0054 Iss 3
Copyright © Gill Instruments 2020

Gill Instruments Ltd, Reg No. 2281574
Registered Office: Towngate House, 2-8 Parkstone Road, Poole. BH15 2PW

¹ Requires a spacer for 144x144 cut-out (retrofit)